
ROS2: Path Planning

운영체제의 실제 안인규 (Inkyu An)






 Path planning is the process of finding the most efficient route from a start point to a goal while avoiding obstacles



 Path planning is the process of finding the most efficient route from a start point to a goal while avoiding obstacles

• In this lecture, we assume that the locations of all obstacles are


known.




- Configuration space
 - The 'world' has two entities: **robots and obstacles**. Both considered as closed subsets of the world (or workspace)
 - The 'space' for motion planning is the set of possible transformations that could be applied to the robot (considered as a rigid body)
 - We refer to this as the configuration space
 - Important abstraction that allows to use the same motion planning algorithms to problems that differ in geometry and kinematics


- Configuration space
 - The 'world' has two entities: **robots and obstacles**. Both considered as closed subsets of the world (or workspace)
 - The 'space' for motion planning is the set of possible transformations that could be applied to the robot (considered as a rigid body)
 - We refer to this as the configuration space
 - Important abstraction that allows to use the same motion planning algorithms to problems that differ in geometry and kinematics


- Configuration space
 - The robot is mapped to a single point in C-space
 - Complete specification of robot configuration can be described by a vector of generalized joint coordinates
 - Each coordinate can be:
 - an angle (for a rotational joint)
 - a length (for a sliding joint)






- Configuration space
 - The robot is mapped to a single point in C-space
 - Complete specification of robot configuration can be described by a vector of generalized joint coordinates
 - Each coordinate can be:
 - an angle (for a rotational joint)
 - a length (for a sliding joint)







- Configuration space
 - How to compute C_{obs} (obstacle C-space) and C_{free} (free C-space)?

Example 1:






Example 2:



Various methods, e.g., reflection points, <u>Minkowski</u> <u>sum</u>, convex Hull.


- Minkowski Sum
 - In geometry, the Minkowski sum of two sets of position vectors A and B in Euclidean space is formed by adding each vector in A to each vector in B, i.e., the set:

$$A \oplus B = \{a + b | a \in A, b \in B\}$$



- Minkowski Sum
 - 로봇 A가 q 위치로 이동:

$$A + q = \{a + q | a \in A\}$$




- Minkowski Sum
 - 로봇 A가 q 위치로 이동:

$$A + q = \{a + q | a \in A\}$$

• 충돌이 발생!

$$A + q \cap B \neq \emptyset$$



- Minkowski Sum
 - 로봇 A가 q 위치로 이동:

$$A + q = \{a + q | a \in A\}$$

• 충돌이 발생!


$$A + q \cap B \neq \emptyset$$

• 즉, A+q와 B에 모두 속하는 q 위치 (vector)가 존재:


$$a + q = b$$

$$q = b - a$$


$$\{(-a) + b | a \in A, b \in B\} = -A \oplus B$$



Occupied C-space




 Assume a workspace, obstacle region, and configuration, with definitions of free and occupied C-spaces




- Path planning approaches
 - Combinatorial (조합론) planning (exact)
 - Sampling-based planning (Probabilistic)
 - Potential-field methods

- Combinatorial methods:
 - 1. Compute C-space
 - 2. Generate a roadmap (i.e., a graph) in C-space
 - Cell decomposition methods: visibility graphs / Voronoi cells / occupancy grid maps
 - A valid roadmap guarantees accessibility and is connectivity preserving w.r.t. C-space
 - 3. Compute the minimum-cost path from initial to goal configuration (cast as a graph search algorithm)



Path Planning – A* algorithm

- How to search roadmap for minimum-cost path?
- One well-known example: A* algorithm
- Extension of Dijkstra' search algorithm, to reduce number of states explored (exploiting an informed search using a heuristic)
- A* plans path from start state to end state
- Forward search, applied to path planning:
 - Evaluation function: f(n)=g(n)+h(n)
 - Operating cost function g(n): cost of path already traversed
 - Heuristic function h(n): information used to find promising nodes to traverse; heuristic must be **admissible** (허용되는) (i.e., must underestimate true cost: $h(n) \le h^*(n)$)



Path Planning – A* algorithm

- Requirements
 - Preprocessing to generate roadmap (connected graph) that represents free C-space
- Pros
 - Optimal path cost and complete
- Cons
 - Memory inefficient
 - Curse of dimensionality

Path Planning – A* algorithm

• A* algorithm vs. Dijkstra's algorithm

